



HUNTER
POLYURETHANE EQUIPMENT

JLB Metering Pump

(Drop in replacement for REXROTH A2VK)


Available in Sizes 6,12,28,55,107,225

Call for pricing and availability



EXPLODED VIEW

All parts are easily made available from OEM
at reasonable prices



- | | | |
|----------------------------------|---------------------|---------------------|
| 1. Front cover | 17. Bearing | 33. Handwheel |
| 2. Spacer ring | 18. Shaft key | 34. Handle |
| 3. Shaft seal ring | 19. Drive shaft | 35. Running bush |
| 4. Square ring | 20. Seal bush | 36. Shaft seal ring |
| 5. Seal bush | 21. Slide ring | 37. Spacer ring |
| 6. Retaining ring | 22. Pin | 38. Cover |
| 7. Shiw | 23. Swivel housing | 39. Bearing |
| 8. Flange(high pressure) | 24. Retaining plate | 40. Spacer ring |
| 9. Safety valve | 25. Piston | 42. Gasket |
| 10. Flange (low pressure) | 26. Center pin | 43. Ring nut |
| 11. Flange housing | 27. Cylinder | 44. Control head |
| 12. Gasket | 28. Control pate | 45. Nut |
| 13. Ball bearing | 29. Port plate | 46. Shaft key |
| 14. Spacer bush | 30. Housing | 47. Cup spring |
| 15. Angular contact ball bearing | 31. Bush | 48. Guide disk |
| 16. Running bush | 32. Cover | 49. Spindle |

1 Pumps fitted with variable displacement control should not be operated at less than 10% of full displacement.



2 Variable displacement axial piston pump for pumping and metering polyurethane components (polyol and isocyanate).



3 Imported materials and bearings make our products more reliable.



4 Special surface treatment ensure the good performance and quality.



5 The operators can precise adjustment of output.





FEATURES

- High metering accuracy and reproducibility of the variable pumped volumes.
- Robust manual adjustment via handwheel with integral precision measuring scale.
- Operating pressure up to 250 bar.
- Low pulsation of the pumped medium.
- Pump components are compatible with the pumped media (polyol, isocyanate) due to special pairings of materials and sealing elements.
- Low-noise
- Excellent volumetric efficiency for high metering accuracy.
- Double shaft seals with buffer fluid ports to guarantee safe operation (and protect the environment).
- With corrosion protection.



HUNTER
POLYURETHANE EQUIPMENT

Contact: Jeff@HunterPURE.com

Website: WWW.HunterPURE.com

Phone: +1-330-801-6766